


◆ LFC Class A Bench-top Oven

High performance laboratory oven for use with flammable solvents

The LFC Class A bench-top oven is specially designed to meet NFPA 86 requirements for applications that include flammable solvents or large amounts of moisture removal. They include a pressure relief panel, purge timer and exhaust fan. The LFC uses horizontal recirculating airflow to ensure uniform temperatures throughout the oven. A high-volume fan circulates air through perforated, stainless steel walls to create a constant horizontal airflow across all sections of the oven. The result is proven reliability in demanding production and laboratory applications such as curing, drying, sterilizing, aging and other process-critical procedures.



Oven control. Standard digital controls regulate temperatures within tight tolerances and provide high limit protection. For more advanced control choose the optional Protocol 3™ microprocessor-based temperature and hi-limit controller with large LCD display and real time clock for auto start capability. Data-logging functionality enables reporting and analyzing and data files can be exported via the controller's USB port. Modbus RS485 communications are included for easy data access.

Easy to clean and service. Cleaning is easy due to the scratch-resistant, baked enamel exterior, 304 stainless steel interior, and smooth door surface. Servicing is easy due to convenient top access to the heater and fan.

Superior quality. The Despatch LFC features sturdy, welded, double-wall construction, three inches (7.6cm) of glass fiber insulation and heavy-duty gaskets. Each oven receives a thorough quality and performance test before it is shipped. Heating elements carry a five-year warranty. All models have UL/C-UL listed 508A control panels



FEATURES AT A GLANCE

- ◆ 3.8, 12, and 27 cu ft (105, 340, and 765 liter)
- ◆ Maximum temperature of 260° C (500° F)
- ◆ Class A package meeting NFPA 86 requirements for flammable solvents
- ◆ High limit over-temperature protection
- ◆ Digital control with 3/4" (1.9cm) LED display
- ◆ Robust type 304 stainless steel interior
- ◆ 5 year heater warranty

NEW LFC2-27

*Shown with
optional
Protocol 3
controller*



LFC	1-38 (240V)	2-12	2-27
PHYSICAL SPECIFICATIONS			
Chamber size (width x depth x height) <i>* Clear opening width is reduced by 3/4" (1.9 cm) due to 3/8" (.95 cm) shelf supports on each side.</i>	19* x 18 x 19 in. 48* x 45 x 48 cm	24* x 24 x 36 in. 61* x 61 x 91 cm	32* x 29 x 52 in. 81* x 74 x 132 cm
Capacity in cubic feet (liters)	3.8 (105)	12 (340)	27(765)
Overall size (width x depth x height)	31 x 33 x 38 in. (78 x 84 x 97 cm)	36 x 39 x 55 in. 91 x 100 x 139 cm	45 x 37 x 83 in. 113 x 94 x 210 cm
Electrical single phase 50/60 HZ <i>* Operating at 208V will result in a 25% reduction in heater output. (Unless conversion kit is used)</i>	240* volt 22.7 amp Heater: 4.8 KW	240* volt 29.1 amp Heater: 6.0 KW	240* volt 59 amp Heater: 12 KW
Number of shelves provided	2		
Maximum number of shelves on 2 in. (5 cm) centers	9	17	25
Shelf dimensions (width x depth)	18.75 x 17.75 in. 48.6 x 45 cm	23.75 x 23.75 in. 60.3 x 60.3 cm	28.6 x 31.8 in. 72.6 x 80.8 cm
Exhaust diameter located on back	4 in (10.2 cm) opening	4 in (10.2 cm) opening	3.55 x 13.5 in. opening
Cord and plug	None - Hardwire		
Number of doors	1	1	2
Approximate domestic shipping weight (export adds weight)	185 lbs (84 kg)	370 lbs (168 kg)	TBD
Approximate domestic shipping weight (export adds weight)	290 lbs (132 kg)	490 lbs (222 kg)	TBD
FUNCTIONAL SPECIFICATIONS			
Time to temperature with no load (40°C to 100°C)	4 minutes	5 minutes	22 minutes
Time to temperature with no load (40°C to 177°C)	-	-	28 minutes
Time to temperature with no load (40°C to 200°C)	13 minutes	18 minutes	27 minutes
Time to temperature with no load (40°C to 260°C)	20 minutes	30 minutes	30 minutes
Temperature uniformity	+/- 1°C at 100°C, +/- 2°C at 177°C (2-27 model only), +/- 2°C at 200°C, +/- 3°C at 260°C for all models		
Operating range with 20°C ambient	40°C -260°C (104°F-500°F)		
Control stability	+/- 0.5°C		
Repeatability	+/- 0.5°C		
Maximum load capacity	175 lbs. (79 kg)	300 lbs. (136 kg)	600 lbs. (272 kg)
Maximum shelf capacity	50 lbs. (23 kg)	50 lbs. (23 kg)	50 lbs. (23 kg)
Solvent handling capacity at 177°C (350°F)	0.02 G.P.H. (0.076 LPH) Toluene or equivalent	0.02 G.P.H. (0.076 LPH) Toluene or equivalent	0.05 G.P.H. MEK
Exhaust capacity	20-50 CFM (9.4- 23.6lps)	20-50 CFM (9.4- 23.6lps)	54-350 CFM (25.5- 165.2lps)
Recirculating fan	1/4 HP 300 CFM (141 lps)	1/2 HP (2-1/4 HP) 600 CFM (282 lps)	1 HP

Notes: Design uniformity figures are based on a nine-point test conducted in an empty oven after stabilization period. Minimum operating temperature and cooling times are based on 20°C ambient temperature measured at the fresh air inlet. Specifications are subject to change without notice. If the existing specifications differ from yours, ask about our customizing capabilities.

* Recovery time as measured at control thermocouple.

OPTIONS

- ◆ Protocol 3™ control with integrated data logging capabilities and USB port for simple oven set-up and data export
- ◆ Door interlock switch turns off heater and fan when door is opened
- ◆ Chart recorders
- ◆ 2" and 4" access port for test wires
- ◆ Oven stand
- ◆ Extra shelves
- ◆ Reinforced shelves 200lb (91Kg) capacity (LFC2-12 only)
- ◆ CE compliance
- ◆ 208V full performance package
- ◆ End-of-cycle and high-limit indicators



SERVICE AND TECHNICAL SUPPORT

service phone: 1-800-737-8110
service international: 1-573-317-3054

dpsupport@itweae.com
parts@itweae.com

GLOBAL HEADQUARTERS

main phone: 1-800-726-0110
international/main: 1-952-469-5424
sales: 1-800-726-0550
international/sales: 1-952-469-8240
sales@despatch.com

WWW.DESPATCH.COM

8860 207th Street West
Minneapolis, MN 55044 USA

Despatch
Thermal Processing Technology **ITW EAE**